



















- [23] J. Ye and Q. Li, A two-stage linear discriminant analysis via QR-decomposition, *IEEE transaction on pattern analysis and machine intelligence*, 27, 2005, (6), pp. 929–941.
- [24] C.F. Vanloan, Generalizing the singular value decomposition, *SIAM J. numerical analysis*, 13, 1976, pp. 76–83.
- [25] G.H. Golub, C.F. Vanloan, Matrix computations, third ed. *the johns hopkins univ. press*, 1996.
- [26] C.C. Paige, M.A. Saunders, Towards a generalized singular value decomposition, *SIAM J. numer. anal.*, 18, 1981, (3), pp. 398–405.
- [27] P. Howland, H. Park, Equivalence of several two-stage methods for linear discriminant analysis, in: *proceedings of the fourth SIAM international conference on data mining*, 4, 2004, pp. 69–77.
- [28] H. Park, M. Jeon, J. Rosen, lower dimensional representation of text data based on centroids and least squares, *BIT*, 43, 2003, (2) pp. 1–22.
- [29] L.M. Zhang, L.S. Qiao, S.C. Chen, Graph-optimized locality preserving projections, *pattern recognition*, 43, 2010, (6), pp. 1993–2002.
- [30] ORL database  
<<http://www.uk.research.att.com/facedatabase.html>>, 2002.
- [31] Yale database  
<<http://cvc.yale.edu/projects/yalefaces/yalefaces.html>>, 2002.
- [32] JianQiang Gao, Liya Fan, Kernel-based weighted Discriminant Analysis with QR Decomposition and Its Application Face Recognition. *WSEAS Transactions on Mathematics*, 10, 2011, (10), pp. 358–367.