
$$L_m = 0.034H$$

Turbine nominal parameters

Number of blades = 3 , Diameter = 60 m

Gearbox = 70

DFIG + Turbine parameters

$J = 32 \text{Kg.m}^2$, $f = 0.046 \text{N.m.d / rad}$

References:

- [1] C. NICHITA, D. LUCA, B. DAKYO, E. CEANGA, and N. A. CUTULULIS, "Modelling non-stationary wind speed for renewable energy systems control," *The annals of "Dunarea de Jos" University of Galati, Fascicle III*, pp. 29–34, 2000.
- [2] M. Arifujjaman, "Vector control of a dfig based wind turbine," *Journal of Electrical and Electronics Engineering*, vol. 2, no. 9, pp. 1057–1065, 2009.
- [3] I. Munteanu, A. I. Brateu, N. A. Cutululis, and E. Ceanga, "Optimal control of wind energy systems," *Springer*, 2008.
- [4] Z. M. Lubosny and B. Anjan, "Wind turbine operation in electric power systems," *Springer*, 2003.
- [5] M. GOSSA, K. JEMLI, M. B. MOHAMED, and M. JEMLI, "Doubly fed induction generator (dfig) in wind turbine, modeling and power control," *IEEE International Conference on Industrial Technology*, pp. 580–584, 2004.
- [6] F. Poitiers, B. Toufik, and A. Machmoum, "Advanced control of a doubly-fed induction generator for wind energy conversion," *Electric Power Systems Research*, no. 79, pp. 1085–1096, 2009.
- [7] H. Bekka, S. Taraft, D. Rekioua, and S. Bacha, "Power control of a wind generator connected to the grid in front of strong winds," *Journal of Electrical Systems*, vol. 3, no. 9, pp. 267–278, 2013.
- [8] D. Rekioua, "Wind power electric systems: Modeling, simulation and control, green energy and technology," *Springer*, 2014.
- [9] A. Boyette, P. Poure, and S. Saadate, "Direct and indirect control of a doubly fed induction generator wind turbine including a storage unit," in *32th edition of Industrial Electronics Conference IECON'2006, IEEE*, Paris, France, November 6-10 2006, pp. 2517–2522.
- [10] A. Tapia, G. Tapia, J. X. Ostolaza, and J. R. Saenz, "Modeling and control of a wind turbine driven doubly fed induction generator," *IEEE Transactions on Energy Conversion*, vol. 18, no. 2, pp. 194 – 204, June 2003.
- [11] R. PENA, J. C. CLARE, and G. M. ASHER, "Doubly fed induction generator using back-to-back pwm converters and its application to variable- speed wind-energy generation," *IEE Puoc.-Electr. Power Appl*, vol. 143, no. 3, May 1996.
- [12] M. LOPEZ, "Contribution à l'optimisation d'un système de conversion éolien pour une unité de production isolée," Ph.D. dissertation, Sciences et Technologies de l'Information des Télécommunications et des Systèmes Université Paris Sud 11, France, 2008.
- [13] G. A. Smith and K. A. Nigim, "Wind-energy recovery by a static scherbius induction generator," in *Proc. IEE*, 1981, pp. 317–324.
- [14] N. CHERFIA, D. KERDOUN, and A. BOUMASSATA, "Correction of the mechanical speed for the dfig wind turbine," *International Journal of Research in Engineering and Technology*, vol. 2, no. 11, pp. 29–38, November 2014.
- [15] H. K. Davijani, A. Sheikholeslami, H. Livani, and M. K. Davijani, "Fuzzy logic control of doubly fed induction generator wind turbine," *World Applied Sciences Journal*, vol. 6, no. 4, pp. 499–508, 2009.
- [16] M. GODOY, B. SIMGES, K. BOSE, and R. J. SPIEGEL, "Fuzzy logic based intelligent control of a variable speed cage machine wind generating system," in *PESC*, 1995.